

TWO-COMPONENT LOW PRESSURE A-COMPONENT

(Silent Seal NA)

MSDS # A16177A

Issue Date: October 2010 Last Rev: October 21, 2010

M A T E R I A L S A F E T Y D A T A S H E E T

1. PRODUCT & COMPANY IDENTIFICATION

Chemical Product

A-Component for Two-Component Low Pressure Polyurethane Foam System for Professional Use in Mining Applications.

Manufacturer

FOMO PRODUCTS, INC.
P. O. Box 1078
Norton, Ohio 44203

Emergency Overview

Product Information: 1-800-321-5585 (Monday-Friday 8:00am-5:00pm). In Ohio and outside the United States call (330) 753-4585.

Transportation Emergency: CHEMTREC 1-800-424-9300 (24 hours). Two-Component A-Component is registered by the manufacturer, FOMO PRODUCTS, INC.

International Transportation Emergency: CHEMTREC (703) 527-3887

Product is a urethane foam component that contains a liquified compressed gas blowing agent (Non-Flammable Compressed Gas). Containers should not be heated above 120°F (49°C) to avoid excessive pressure build-up.

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING! EYE, SKIN, LUNG IRRITANT. May cause eye irritation. May cause skin irritation. May cause allergic skin reaction. Skin Sensitizer. May cause allergic respiratory reaction. Harmful if inhaled. May cause lung injury. Respiratory sensitizer. Lung damage and respiratory sensitization may be permanent. May cause central nervous system effects. Keep upwind of spill. May cause anesthetic effects. Pressurized Containers: storage temperature should not exceed 120°F (49°C) in order to avoid excessive pressure build-up and possible release of contents. MDI will react with water to form CO₂ and water insoluble polyureas.

Potential Health Effects

The primary adverse health effects of this product are related to the Polymeric Isocyanate (MDI) component, and, to a lesser degree, the Fluorocarbon (134a) component.

Entry Route: Effects of Overexposure

Inhalation: May irritate mucous membranes. Can cause runny nose, sore throat, coughing, chest discomfort, shortness of breath, wheezing, and reduced lung function. Extensive overexposure can lead to respiratory symptoms like bronchitis, bronchial spasm, and pulmonary edema. These symptoms could be immediate or delayed up to several hours after exposure. These effects are usually reversible, but increased lung sensitivity can persist for a longer period of time. Chronic overexposure to diisocyanates can cause permanent damage. Overexposure to 1,1,1,2 - Tetrafluoroethane may cause lightheadedness, headaches, or lethargy. Persons with cardiac arrhythmia are more susceptible to increased medical risks from severe exposure.

- Eyes:** May be irritating to eyes. Symptoms of irritation can include reddening, tearing, swelling, or stinging. May cause temporary corneal injury. Chronic overexposure may cause conjunctivitis.
- Skin:** May cause localized irritation, reddening or swelling. May cause an allergic reaction. Prolonged or repeated exposure may lead to sensitization and/or contact dermatitis.
- Ingestion:** May cause irritation of mucous membranes in the mouth and digestive tract. Symptoms may include abdominal pain, nausea, vomiting, and diarrhea. Small amounts are unlikely to cause symptoms or injury.

If accidental contact occurs, follow the appropriate first aid procedure described in Section 4 of this MSDS.

3. COMPOSITION

<u>Chemical Name (common names)</u>	<u>CAS Number</u>	<u>Percentage</u>
1,1,1,2- Tetrafluoroethane (Non-Flammable Compressed Gas, HFC, Fluorocarbon) 134a	811-97-2	5 to 10 percent
4,4' - Diphenylmethane Diisocyanate (MDI)	101-68-8	30 to 60 percent
Higher Oligomers of MDI (Polymeric MDI)	9016-87-9	30 to 60 percent

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

(NOTE: See Section 11 of this MSDS for Toxicological Information- LC₅₀ and LD₅₀)

4. FIRST AID

- Inhalation:** If breathing difficulty is experienced, move to area free of exposure. Provide fresh air. If necessary, provide oxygen or artificial respiration by trained personnel and obtain medical attention.
- Eye Contact:** Flush with clean water for at least 15 minutes and obtain medical attention.
- Skin Contact:** Use a rag to remove liquid from skin and remove contaminated clothing. May cause mild irritation or temporary darkening of skin. Persistent washing with soap and water will eventually remove all residues. If irritation persists, obtain medical attention.
- Ingestion:** Drink 1 to 3 glasses of water and seek immediate medical attention. Do not induce vomiting. Never give anything orally to an unconscious person.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical, carbon dioxide, Halon 1211, chemical foams, or water spray (if used in large quantities).

Firefighting Procedures: Isolate area. Stay upwind. Water is not recommended unless used in large quantities as a fine spray when other extinguishing agents are not available. The product is equipped with a pressure relief valve which can activate in a high temperature situation. Remove all personnel from the area at the first sound of releasing pressure. Protective equipment: Wear self-contained breathing apparatus to protect against toxic decomposition by-products, including Carbon monoxide, Carbon dioxide, Nitrogen oxides, Isocyanates, Hydrogen fluoride and traces of Hydrogen cyanide. Wear all turn out gear (boots, trousers, helmet, gloves, and hood).

Unusual Fire/Explosion Hazards: Product reacts with water. Water Contamination will produce carbon dioxide. High temperatures will raise the pressure in the containers, which may lead to rupturing. Cured foam is organic and, therefore, will burn in the presence of sufficient heat, oxygen and an ignition source. Main hazards associated with burning foam are similar to burning of other organic materials (wood, paper, cotton, etc.) and precautions against exposure should be taken accordingly. Avoid welding or other "hot work" in the vicinity of exposed cured foam.

6. ACCIDENTAL RELEASE MEASURES/DISPOSAL CONSIDERATIONS

Personal Precautions: Evacuate all unnecessary personnel; contain the area if possible. Wear skin and eye protection equipment. Ventilate the area.

Environmental Precautions: Containment should include preventing the spill from entering drains, sewers, waterways, groundwater, or soil.

Clean Up Procedures/Neutralization: Soak up material with absorbent and shovel into chemical waste container. Loosely cover container and remove from work area. Decontaminate waste and spill area with a solution of 0.2 – 0.5% liquid detergent and 3 – 8% concentrated ammonium hydroxide in water (5 – 10% sodium bicarbonate may be substituted for ammonium hydroxide). Use 10 parts of solution for each part of the spill and allow to react for at least 10 minutes. Allow loosely covered container to stand for several days before disposing in accordance with all applicable federal, state and local regulations.

7. HANDLING AND STORAGE

Handling: Use only in a well ventilated area. Wear protective glasses or goggles, nitrile gloves, and clothing that protects from dermal exposure. Contents are under pressure. Do not puncture or incinerate.

Storage: Store in a dry place. Ideal storage temperature for disposable kits is 60°F to 80°F (15.5°C to 26.6°C). Store refillable tanks at 75°F to 85°F (24°C to 29°C). Storage at less than ideal temperatures can cause delays in production until the product is warmed/cooled to temperature. Do not expose the tanks/kits to open flame or temperatures above 120°F (49°C). Excessive heat can cause premature aging of components resulting in a shorter shelf life. Protect unused product from freezing. Storage below 55°F (12.7°C) may affect foam quality if chemicals are not warmed to room temperature before using. Protect containers from physical abuse. Store containers upright.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Read all product instructions before using.

Exposure Guidelines

4,4' – Diphenylmethane Diisocyanate (MDI)	<u>OSHA</u> <u>ACGIH</u>	.020 ppm ceiling .005 ppm TWA	200 mg/m ³ ceiling .051 mg/m ³ TWA
1,1,1,2 - Tetrafluoroethane	<u>WEEL</u>	1,000 ppm	4,240 mg

(None of the components in this product are listed by IARC, NTP, OSHA or ACGIH as a carcinogen).

Personal Protective Equipment in Ventilated Underground Applications

Silent Seal NA has been found suitable according to MSHA Standard 30 CFR 75.333 (Ventilation Controls). Based on studies conducted by MSHA PSHTC, Silent Seal Foam (Suitability Number: MSHA S10/00) does not create a harmful environment for workers when applied within 24 inches of the structure being sealed. It is not necessary for applicators to wear respiratory protection. Ventilation controls must be in place.

Note: In applications other than underground mining please contact Fomo Products Inc (1.800.321.5585) for guidance. A respirator with organic cartridges may be required.

Hand Protection: Use chemically resistant gloves (ie Nitrile gloves). Nitrile/butadiene rubber, Butyl Rubber, polyethylene, PVC (vinyl), or neoprene gloves are also effective. Glove selection should take into account potential body reactions to certain materials and manufacturer's instructions for use.

Eye Protection: Use safety glasses or goggles. An eye wash station or portable eye wash bottle should be in the area.

Skin Protection: Avoid contact with skin. Use clothing that protects against dermal exposure.

Medical Surveillance: Users whom have a history of adult asthma should be excluded from work with isocyanates. Some users can become sensitized to isocyanates. Once a user has become sensitized, no further exposure should be permitted. Skin or respiratory allergies should also be taken into account when using isocyanates.

General Hygiene: Do not eat, drink, or eat while handling this product. Always use in a well ventilated area. Wash after handling. Do not breathe vapors. Avoid contact with skin and hands.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Amber to dark brown liquid. Froths to an off white to yellowish color when released from the container. (Note: Appearance may differ with the introduction of a dye/colorant.
Odor:	Slight Musty odor
pH:	Not available
Melting/Freezing Point:	Not available
Boiling Point:	1,1,1,2 - Tetrafluoroethane (Non-Flammable Compressed Gas, HFC Fluorocarbon 134a) boils at -15°F (-26°C). MDI boils at 406°F (208°C).
Flash Point:	1,1,1,2 - Tetrafluoroethane (HFC 134a); none. MDI; 390°F (199°C).
Specific Gravity:	Approximately 1.2 (H ₂ O = 1) at 25°C
Solubility:	Water: Insoluble reacts slowly with water to liberating traces of CO ₂ .
Partition Coefficient N-octanol/water:	Not available
Auto-ignition Temperature:	Not available
Decomposition Temperature:	Not available
Odor Threshold:	Not available
Evaporation Rate:	Not available
Flammability:	Non flammable propellant
Flammability Limits:	Not available
Vapor Pressure:	Contents under pressure have vapor pressure greater than 50 psig/345 kPa. For MDI liquid less than 10 mm Hg at 77°F (25°C).
Vapor Density:	Not available

10. STABILITY AND REACTIVITY

Stability: This product is considered stable under normal and anticipated storage and handling conditions. Do not store above 120°F (49°C). For longest shelf life, avoid storage above 90°F (32.2°C).

Materials to Avoid: Alcohols, strong bases or amines, metal compounds, ammonia, strong oxidizers. Avoid contamination with water.

Conditions to Avoid: Avoid moisture. Material reacts slowly with water, releasing CO₂. High temperatures will raise the pressure in the containers, which may lead to rupturing. Product use is temperature sensitive. Avoid temperatures below 40°F (5°C) or temperatures above 95°F (35°C).

Thermal Decomposition: Toxic decomposition by-products, including Carbon monoxide, Carbon dioxide, Nitrogen oxides, Isocyanates, Hydrogen fluoride and traces of Hydrogen cyanide can be released in instances of fire.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Inhalation: LC50 490 mg/m³ (4h, rat)

Ingestion: LD50 >5,000 mg/kg (rat, male/female)

Skin: LD50 >5,000 mg/kg (rabbit)

Sensitization

Skin: (rabbit, slightly irritating)

Eye: (rabbit, slightly irritating)

Repeated Dose Toxicity: 2 yrs, Inhalation, NOAEL .19, (rat, male/female, 6hrs/day, 5days/week) Irritation to lungs and nasal cavity

Chronic Toxicity/ Carcinogenicity: 6.3 mg/m (high level of exposure, 2years, 6hrs/day, 5days/week) Lung tumors observed.

Developmental Toxicity: rat, female, 6hrs/day, 12 mg/m³, days 6-15 (gestation period); 4 mg/m³ (maternal/fetotoxicity)

Genetic Toxicity In vitro: Inconclusive, In vitro studies were negative/positive, salmonella typimurium

12. ECOLOGICAL INFORMATION

Ecological Data for Polymeric MDI:

Biodegradation: Expected to have a short half-life

Bioaccumulation: Oncorhynchus mykiss (rainbow trout), 112 day exposure, <1 BCF. Does not bioaccumulate.

Acute Toxicity to Fish: LC0: >1000mg/l brachydanio rerio (zebra fish), 96 hour exposure

Acute Toxicity to Aquatic Invertebrates: EC50: >1000 mg/l Daphnia magna (water flea), 24h

Toxicity to Microorganisms: EC50: >100 mg/l, activated sludge, 3h

Ecological Data for MDI

Acute Toxicity to Fish: LC50: >500mg/l brachydanio rerio (zebra fish), 24h

Acute Toxicity to Aquatic Invertebrates: EC50: >500 mg/l Daphnia magna (water flea), 24h

Ecological Data for 1,1,1,2-Tetrafluoroethane

Accumulation in aquatic organisms is unlikely

13. DISPOSAL CONSIDERATIONS

Disposable Cylinders:

1. DO NOT INCINERATE TANKS

2. After tanks are empty, the hose must be removed and the tanks must be vented. CAUTION: Tanks will still be under pressure. Turn valves to the off position before removing the hoses. Safety glasses or goggles, nitrile gloves, and clothing that protects against dermal exposure must be worn during this procedure. With tank inverted, slowly open tank valve, point tank away from face and allow pressure to completely vent. CAUTION: Empty tank could contain potential vapor toxicity hazard. Only dispose cylinders in a well ventilated area.

3. DISPOSE OF EMPTY CYLINDERS ACCORDING TO APPLICABLE FEDERAL, STATE, PROVINCIAL AND LOCAL REGULATIONS. CHECK WITH YOUR LOCAL WASTE DISPOSAL SERVICE FOR GUIDANCE.

Refillable Tanks:

THESE TANKS ARE RETURNABLE.

The tanks are shipped back to Fomo Products, Inc to be cleaned, refilled, and redistributed. Return instructions are included in the collar of the refill tanks.

14. TRANSPORTATION

	Containers Less Than 1000 cu. cm. (1 liter)	Containers Greater Than 1000 cu. cm. (1 liter)
<i>Ground DOT</i>	Consumer Commodity ORM-D (On Shipper Carton) Consumer Commodity Two-Component A-Component (On Shipping Document)	UN1956 Compressed Gas n.o.s. (Fluorocarbon) 2.2 (Non-Flammable Gas Label)
<i>Air IATA</i>	UN1950 Aerosols, Non-Flammable 2.2 (Non-flammable Gas Label) LIMITED QUANTITY Packing Instruction (Cargo & Passenger) 203	UN1956 Compressed Gas n.o.s. (Fluorocarbon) 2.2 (Non-flammable Gas Label) Packing Instruction (Cargo & Passenger) 200
<i>Water IMDG</i>	UN1950 Aerosols, Non-Flammable 2.2 LIMITED QUANTITY	UN1956 Compressed Gas n.o.s. (Fluorocarbon) 2.2 (Non-flammable Gas Label)

Note Emergency Response Guide Numbers - Consumer Commodity # 171. For Aerosols and Compressed Gas # 126.

15. REGULATORY

OSHA Hazcom Standard Rating:

Hazardous

WHMIS Classification:A
D1A
D2BToxic Substances Control Act (TSCA)/Domestic Substances List (DSL):

All ingredients are listed on the TSCA inventory, as well as the Canadian Domestic Substances List.

SARA Title III: Section 311/312:

Acute Health Hazard, Chronic Health Hazard, Sudden Release of Pressure Hazard

SARA Title III: Section 313

Contains Diphenylmethane Diisocyanate (CAS #101-68-8) and Diphenylmethane Diisocyanate, Isomers and homologues (CAS #9016-87-9) which are subject to the reporting requirements of SARA Title III. Applicability must be determined by end user.

State Right-To Know Information: Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

<u>Chemical Name (common names)</u>	<u>CAS Number</u>	<u>Percentage</u>
Diphenylmethane Diisocyanate	101-68-8	5% to 10 %

California Proposition 65:

Based on information currently available, this product is not known to contain detectable amounts of any chemicals currently listed under California Proposition 65.

16. OTHER

NFPA: Health Hazard 2; Flammability 1; Reactivity 1**HMIS III: Health 2*; Flammability 1; Physical Hazard 1**

* =chronic health hazard

The information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, of merchantability or fitness for a particular use are made hereunder with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. Fomo Products, Inc. reserves the right to change the design, specifications or any other features at any time and without notice, while otherwise maintaining regulatory compliance.

LAST REVISION: OCTOBER 2010-0 A16177-A Product Management