

TWO-COMPONENT B-COMPONENT

(Sound Barrier and Low Density)

MSDS # A16180B

Issue Date: January 2010 Last Rev: January 28, 2010

M A T E R I A L S A F E T Y D A T A S H E E T

1. PRODUCT & COMPANY IDENTIFICATION

Chemical Product

B-Component for Two-Component Polyurethane Foam System

Manufacturer

FOMO PRODUCTS, INC.
P. O. Box 1078
Norton, Ohio 44203

Emergency Overview

Product Information: 1-800-321-5585. In Ohio and outside the United States call (330) 753-4585
Transportation Emergency: CHEMTREC 1-800-424-9300. Two-Component B-Component is registered by the manufacturer, FOMO PRODUCTS, INC.
International Transportation Emergency: CHEMTREC (703) 527-3887

Product is a urethane foam component that contains a liquified compressed gas blowing agent (Non-Flammable Compressed Gas). Containers should not be heated above 120°F (49°C) to avoid excessive pressure build-up.

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING! EYE, SKIN, LUNG IRRITANT. May be harmful if inhaled. Vapor reduces oxygen available for breathing. May cause lung injury. Respiratory sensitizer. May cause central nervous system effects. May cause liver damage. Toxic gases/fumes may be given off during burning. Storage Temperature should not exceed 120°F (49°C) in order to avoid excessive pressure build-up and possible release of contents. May cause a temporary fogging of the eyes.

Potential Health Effects

The primary adverse health effects of this product are related to the individual components that make-up the mixture, and the Fluorocarbon (134a) component. Therefore, use in a well ventilated area and with certified respiratory protection to avoid exceeding exposure limits listed in Section 8 of this MSDS.

Entry Route: Effects of Overexposure

Inhalation: Tris (1-chloro-2-propyl) phosphate: Existing medical conditions such as asthma and pulmonary diseases may be aggravated by prolonged exposure. This material is a weak cholinesterase inhibitor. Excessive exposure may result in these symptoms: salivation, sweating, headache, nausea, muscle twitching, incoordination, diarrhea, blurred vision, abdominal cramps, tears, tremor, and chest discomfort.

Ethylene Oxide: Irritating to respiratory system. Avoid breathing vapor or mist.

Tertiary Amine: Can cause severe eye, skin, and respiratory tract burns. May cause nose, throat, and lung irritation. Inhalation of vapors in high concentration may cause irritation of respiratory system.

1,1,1,2- Tetrafluoroethane: Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. May cause central nervous system effects. May cause cardiac arrhythmia. Vapors may cause drowsiness and dizziness.

Alkanolamine: May cause nose, throat, and lung irritation. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Eyes: **Tris (1-chloro-2-propyl) phosphate:** May cause eye irritation.

Tertiary Amine: Can cause severe eye, skin, and respiratory tract burns.

Ethyl Oxide: Severely irritating to eyes. Do not get into eyes.

1,1,1,2- Tetrafluoroethane: Can cause severe irritation, redness, tearing, and blurred vision.

Alkanolamine: Severe eye irritation. Product vapor in low concentrations can cause lacrimation, conjunctivitis and corneal edema when absorbed into the tissue of the eye from the atmosphere. Corneal edema can cause the perception of “blue haze” or “fog” around lights, although this is a temporary effect and has no known residual effect.

Skin: **Tris (1-chloro-2-propyl) phosphate:** Prolonged exposure is unlikely to result in absorption of harmful amounts.

Tertiary Amine: Can cause severe eye, skin, and respiratory tract burns. May cause nose, throat, and lung irritation. Inhalation of vapors in high concentration may cause irritation of respiratory system.

1,1,1,2- Tetrafluoroethane: Irritating to skin, may cause redness, may cause frostbite.

Ethyl Oxide: Slightly irritating to the skin.

Alkanolamine: Prolonged contact may result in chemical burns and permanent damage

Ingestion: **Tris (1-chloro-2-propyl) phosphate:** Existing medical conditions such as asthma and pulmonary diseases may be aggravated by prolonged exposure. This material is a weak cholinesterase inhibitor. Excessive exposure may result in these symptoms: salivation, sweating, headache, nausea, muscle twitching, incoordination, diarrhea, blurred vision, abdominal cramps, tears, tremor, and chest discomfort.

Tertiary Amine: Can cause severe eye, skin, and respiratory tract burns. Harmful if swallowed.

Alkanolamine: Harmful if swallowed

1,1,1,2- Tetrafluoroethane: Unlikely route of exposure. May cause gastrointestinal discomfort.

If accidental contact occurs, follow the appropriate first aid procedure described in Section 4 of this MSDS.

3. COMPOSITION

<u>Chemical Name (common names)</u>	<u>CAS Number</u>	<u>Percentage</u>
Non-Hazardous Polyol Blend	Not Available	30 to 60 percent
Tris (1-chloro-2-propyl) phosphate	13674-84-5	10 to 30 percent
1,1,1,2- Tetrafluoroethane	811-97-2	10 to 30 percent
Tertiary Amine	3030-47-5	0.5 to 1.5 percent
Ethylene Oxide	111-46-6	0.5 to 1.5 percent
Alkanolamine	2212-32-0	0.5 to 1.5 percent
Surfactants	Trade Secret	1 to 5 percent

(NOTE: See Section 8 of this MSDS for Exposure Guidelines)

(NOTE: See Section 11 of this MSDS for Toxicological Information- LC₅₀ and LD₅₀)

4. FIRST AID

- Inhalation:** If breathing difficulty is experienced, move to area free of exposure. Provide fresh air. If necessary, provide oxygen or artificial respiration by trained personnel and obtain medical attention.
- Eye Contact:** Flush with clean water for at least 15 minutes and obtain medical attention.
- Skin Contact:** Use a rag to remove liquid from skin and remove contaminated clothing. May cause mild irritation or temporary darkening of skin. Persistent washing with soap and water will eventually remove all residues. If irritation persists, obtain medical attention.
- Ingestion:** Drink 1 to 3 glasses of water and seek immediate medical attention. Do not induce vomiting. Never give anything orally to an unconscious person.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical, carbon dioxide, Halon 1211, chemical foams, or water spray (if used in large quantities).

Firefighting Procedures: Isolate area. Stay upwind. Water is not recommended unless used in large quantities as a fine spray when other extinguishing agents are not available. The product is equipped with a pressure relief valve which can activate in a high temperature situation. Remove all personnel from the area at the first sound of releasing pressure. Protective equipment: Wear self-contained breathing apparatus to protect against toxic decomposition by-products, including Carbon monoxide, Carbon dioxide, Nitrogen oxides, Hydrogen fluoride and traces of Hydrogen cyanide. Wear all turn out gear (boots, trousers, helmet, gloves, and hood).

Unusual Fire/Explosion Hazards: High temperatures will raise the pressure in the containers, which may lead to rupturing. Cured foam is organic and, therefore, will burn in the presence of sufficient heat, oxygen and an ignition source. Main hazards associated with burning foam are similar to burning of other organic materials (wood, paper, cotton, etc.) and precautions against exposure should be taken accordingly. Avoid welding or other "hot work" in the vicinity of exposed cured foam.

6. ACCIDENTAL RELEASE MEASURES/DISPOSAL CONSIDERATIONS

Personal Precautions: Evacuate all unnecessary personnel; contain the area if possible. Wear skin, eye, and respiratory protection and equipment (See section 8). Ventilate the area.

Environmental Precautions: Containment should include preventing the spill from entering drains, sewers, waterways, groundwater, or soil.

Clean Up Procedures/Neutralization: Soak up material with sawdust or vermiculite and dispose of in accordance with all applicable federal, state, and local regulations. Wash spill area thoroughly with soap and water. Avoid uncontrolled reactions with isocyanates.

7. HANDLING AND STORAGE

Handling: Use only in a well ventilated area with certified respiratory protection or with a power air purifying respirator (PAPR). Wear protective glasses or goggles, nitrile gloves, and clothing that protects from dermal exposure. Contents are under pressure. Do not puncture or incinerate.

Storage: Store in a cool, dry place. Ideal storage temperature for disposable kits is 60°F to 80°F (15.5°C to 26.6°C). Store refillable tanks at 75°F to 85°F (24°C to 29°C). Storage at less than ideal temperatures can cause delays in production until the product is warmed/cooled to temperature. Do not expose the tanks/kits to open flame or temperatures above 120°F (49°C). Excessive heat can cause premature aging of components resulting in a shorter shelf life. Protect unused product from freezing. Storage below 55°F (12.7°C) may affect foam quality if chemicals are not warmed to room temperature before using. Protect containers from physical abuse.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Read all product instructions before using.

Exposure Guidelines

1,1,1,2 - Tetrafluoroethane	<u>WEEL</u>	1,000 ppm	4,240 mg/m ³
-----------------------------	-------------	-----------	-------------------------

Personal Protective Equipment

Respiratory Protection/Ventilation: Use products only in a well ventilated area. If atmospheric levels are expected to exceed the exposure levels, use a NIOSH approved air purifying respirator equipped with an organic vapor cartridge and a particulate filter (N95). If atmospheric levels exceed 10 times the TLV or PEL level for which an air-purifying respirator is effective, use a powered air purifying respirator (PAPR). The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29 CFR 1910.134). Use local and general exhaust ventilation to control levels of exposure.

Hand Protection: Use chemically resistant gloves. Nitrile/butadiene rubber, Butyl Rubber, polyethylene, PVC (vinyl), or neoprene gloves are also effective. Glove selection should take into account potential body reactions to certain materials and manufacturer's instructions for use.

Eye Protection: Use safety glasses or goggles. An eye wash station should be in the area.

Skin Protection: Avoid contact with skin. Use clothing that protects against dermal exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance:	Light yellow to amber colored liquid. Froths to an off white to yellowish color when released from container. (Note; Appearance may differ with the introduction of a dye or colorant).
Odor	: Slight fluorocarbon and amine odor.
Specific Gravity:	Approximately 1.2 (H ₂ O = 1)
Boiling Point	: 1,1,1,2 - Tetrafluoroethane (Non-Flammable Compressed Gas, HFC Fluorocarbon, 134a) boils at -15°F (-26°C). Other components boil at temperatures greater than 200°F (93.3°C).
Flash Point	: 1,1,1,2 - Tetrafluoroethane (HFC 134a); none. For other components – not determined.
Vapor Pressure	: Contents under pressure have vapor pressure greater than 50 psig /345 kPa. After release from container, the vapor pressure is very low (not determined).
Solubility in Water:	Partly soluble, does not react.
Explosion Data:	Contents are not known to be sensitive to mechanical impact or static discharge.
Vapor Density:	No test data available.
Freezing Point:	No test data available.
pH:	Not applicable

10. STABILITY AND REACTIVITY

Stability: This product is considered stable under normal and anticipated storage and handling conditions. Do not store above 120°F (49°C). For longest shelf life, avoid storage above 90°F (32.2°C).

Materials to Avoid: Alcohols, strong bases or amines, metal compounds, ammonia, strong oxidizers.

Conditions to Avoid: High temperatures will raise the pressure in the containers, which may lead to rupturing. Product use is temperature sensitive. Avoid temperatures below 40°F (5°C) or temperatures above 95°F (35°C).

Thermal Decomposition: Toxic decomposition by-products, including Carbon monoxide, Carbon dioxide, Nitrogen oxides, Hydrogen fluoride and traces of Hydrogen cyanide can be released in instances of fire.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity for Tris (1-chloro-2-propyl) phosphate:

Ingestion: LD50: 2,800 mg/kg (rat, male/female)

Skin: LD50: >5,000 mg/kg, rat

Inhalation: LC50: >4.6 mg/l, rat

Acute Toxicity for Ethylene Oxide:

Ingestion: LD50: 2,000-5,000 mg/kg, rat

Skin: LD50: >2,000 mg/kg, rabbit

Acute Toxicity for Tertiary amine:

Ingestion: LD50: 1630 mg/kg, rat

Skin: LD50: 280 mg/kg, rabbit

Inhalation: LC50: 290ppm, rat, 6h

Acute Toxicity for 1,1,1,2-Tetrafluoroethane:

Inhalation: LC50 >500,000 ppm, rat, 4h

Acute Toxicity for Alkanolamine:

Ingestion: LD50: >1,580 mg/kg, rat

Skin: LD50: >2,000 mg/kg, rabbit

Inhalation: LC50: >20 mg/l, rat, 1h

Repeated Dose Toxicity:

Tris (1-chloro-2-propyl) phosphate which is reported to be a weak organophosphate-type cholinesterase inhibitor.

Excessive exposure may produce organophosphate type cholinesterase inhibition. Symptoms may include salivation, sweating, headache, nausea, muscle twitching, incoordination, diarrhea, blurred vision, abdominal cramps, tears, tremors, and chest discomfort. Target organs: kidney, liver, and or sternal bone marrow.

1,1,1,2-Tetrafluoroethane: NOEL 40000ppm, rat

Tertiary Amine: 12ppm, rat, 2 week inhalation, observed corneal opacities. 48ppm, rat, 2week inhalation, cloudy corneas, skin and respiratory tract irritation.

Mixture contains components which have been reported to cause effects on the following animal organs: liver, central nervous system, and bladder.

Chronic Toxicity/ Carcinogenicity: Components did not cause cancer in laboratory animals.

Developmental Toxicity: Diethylene glycol has caused toxicity to the fetus and some birth defects at maternally toxic, high doses in animals.

Genetic Toxicity In vitro: In vitro studies were negative.

12. ECOLOGICAL INFORMATION

Ecological Data for Tris (1-chloro-2-propyl) phosphate:

Acute Toxicity to Fish: LC50: 84mg/l *Lepomis macrochirus* (bluegill), 96 hour exposure

Acute Toxicity to Aquatic Invertebrates: EC50 63 mg/l *Daphnia magna* (water flea), 48h

Toxicity to Microorganisms: EC50: 784 mg/l, activated sludge, 3h

Ecological Data for Ethylene Oxide:

No data available

Ecological Data for Tertiary amine:

Acute Toxicity to Fish: LC50: 220mg/l *Leuciscus idus* (golden orfe), 96h

Ecological Data for Alkanolamine:

No data available

Ecological Data for 1,1,1,2-Tetrafluoroethane

Accumulation in aquatic organisms is unlikely.

13. DISPOSAL CONSIDERATIONS

Disposable Cylinders:

1. DO NOT INCINERATE TANKS

2. After tanks are empty, the hose must be removed and the tanks must be vented. CAUTION: Tanks will still be under pressure. Turn valves to the off position before removing the hoses. Safety glasses or goggles, nitrile gloves, clothing that protects against dermal exposure, and a certified respirator must be worn during this procedure. With tank inverted, slowly open tank valve, point tank away from face and allow pressure to completely vent. CAUTION: Empty tank could contain potential vapor toxicity hazard. Dispose Cylinders in a well ventilated area with certified respiratory protection.

3. DISPOSE OF EMPTY CYLINDERS ACCORDING TO APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS. CHECK WITH YOUR LOCAL WASTE DISPOSAL SERVICE FOR GUIDANCE.

Refillable Tanks:

THESE TANKS ARE RETURNABLE.

The tanks are shipped back to Fomo Products, Inc to be cleaned, refilled, and redistributed. Return instructions are included in the collar of the refill tanks.

14. TRANSPORTATION

Shipping Information

	Containers Less Than 1000 cu. cm. (1 liter)	Containers Greater Than 1000 cu. cm. (1 liter)
<i>Ground</i>	Consumer Commodity ORM-D (On Shipper Carton) Consumer Commodity Two-Component A-Component (On Shipping Document)	UN1956 Compressed Gas n.o.s. (Fluorocarbon) 2.2 (Non-Flammable Gas Label)
<i>Mining Foam</i>		UN1956 Compressed Gas n.o.s. (1,1,1,2 Tetrafluoroethane) 2.2 (Non-Flammable Gas Label)
<i>Air</i>	UN1950 Aerosols, Non-Flammable 2.2 (Non-flammable Gas Label)	UN1956 Compressed Gas n.o.s. (Fluorocarbon) 2.2 (Non-flammable Gas Label)
<i>Mining Foam</i>		UN1956 Compressed Gas n.o.s. (1,1,1,2 Tetrafluoroethane) 2.2 (Non-Flammable Gas Label)
<i>Water</i>	UN1950 AEROSOLS "LTD QTY" 2 IMDG Volume 2; Page # 93	UN1956 Compressed Gas n.o.s. (Fluorocarbon) 2.2 IMDG Volume # 2; Page # 93
<i>Mining Foam</i>		UN1956 Compressed Gas n.o.s. (1,1,1,2 Tetrafluoroethane) 2.2 (Non-Flammable Gas Label)
<i>Exceptions</i>	N/A	
<i>Note</i>	Emergency Response Guide Numbers - Consumer Commodity # 171. For Aerosols and Compressed Gas # 126.	

15. REGULATORY

OSHA Hazcom Standard Rating:

Hazardous

Toxic Substances Control Act (TSCA)/Domestic Substances List (DSL):

All ingredients are listed on the TSCA inventory, as well as the Canadian Domestic Substances List.

SARA Title III: Section 311/312:

Acute Health Hazard, Chronic Health Hazard, Sudden Release of Pressure Hazard

SARA Title III: Section 313: Does not contain chemicals which require reporting requirements of SARA Title III. Applicability must be determined by end user.California Proposition 65:

This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

<u>Ingredient</u>	<u>Cancer</u>	<u>Reproductive</u>	<u>No significant risk level</u>	<u>Maximum acceptable dosage level</u>
Ethylene oxide	Yes	Yes	Yes	Yes

16. OTHER

NFPA: Fire 1; Health 2; Reactivity 1**HMIS: Flammability 1; Health 2; Reactivity 1**

The information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, of merchantability or fitness for a particular use are made hereunder with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. Fomo Products, Inc. reserves the right to change the design, specifications or any other features at any time and without notice, while otherwise maintaining regulatory compliance.

LAST REVISION : January 2010-0 Product Management**A16180B**